

CFS-MB3 WALL PACK SERIES 40~55 Watts



Ordering Info	
40W	CFS-MB3-40E-ST40W
55W	CFS-MB3-55E-ST55W

Features:

- *Die cast aluminum housing with bronze powder coated finish corrosion-resistance.
- *UV stabilized and heat resistant polycarbonate lens.
- *Anodized aluminum reflector.
- *Gas-tight silicon rubber seal made for wet locations.

Lamps and ballasts:

- *40 and 55W Square type induction lamp with high lighting efficacy at rated 100,000hrs lifetime, about 20 years burning on 4000hrs/year.
- *Electronic ballast features high power factor (>0.95), flickering free, constant output wattage, and safe protection.

Ambient temperature for lighting fixture:

- *-20C~40C.

Applications:

- *Plazas, parks, outlets, city halls, historic areas, shopping malls.

Induction Lighting Features

No electrodes or filaments

- *100,000 hrs rated average life.
- *Low lumen depreciation of <30% @ 60,000 hours.
- *Low operating temperature of components.

High-frequency operation

- *High system efficacy(65-70lm/W)
 - *No flickering
 - *No stroboscopic effect
 - *No noise

Electronic control

- *Output-protected HF generator

Instant (re-)start

- *Light available instantly when needed
- *Short ignition time <0.5sec

3-line fluorescent coating

- *Choice of color temperature
 - *White light
- *Excellent color rendition (CRI 85)
 - *No color deviation

Induction Lighting Benefits

- *High reliability and virtually maintenance-free operation.
 - *Lasting light output right through life time.
- *Increased safety, more standard luminaire construction.
- *Economic, environment-friendly lighting in situations with long burning hours.
 - *Restful non-fatiguing light.
 - *No danger with rotating machinery.
 - *Non-disturbing in operations.
- *Automatic switch-off in case of lamp or power coupler failure.
 - *Generator resets 15-30 seconds after switch off.
 - *Suitable for security and safety lighting.
 - *More comfort.
- *Useful light immediately after switch-on.
- *Installation can be matched to lighting situations and requirements.
- *Uniform predictable lighting results throughout larger installations; color maintained through life.




All CFS Inc. products come with a 5 year warranty.

CFS INC.

3 Adams Street- Belvidere, NJ 07823- Tel: 908-475-8991 Fax: 973-729-1271
E-mail: info@cfsinc.us Web Site: www.cfsinc.us

CFS-MB3 WALL PACK SERIES 40/55 Watt Photometrics



Dimensions

